



REQUEST FOR QUOTATION (RFQ) No. 115-2023

Procurement Unit

The Tarlac State University (TSU), through its Bids and Awards Committee (BAC) and Procurement Unit, will undertake an **Alternative Method of Procurement through Shopping** for the items stated below, in accordance with **Section 52.1(b)** of the Revised Implementing Rules and Regulations of Republic Act. No. 9184.

The TSU hereinafter referred to as "the Buyer", now requests submission of a price quotation for the subject below:

Purchase Request No.	DESCRIPTION/PARTICULARS	APPROVED BUDGET FOR THE CONTRACT (ABC) inclusive of VAT
2023-02-074 (PROC)	VARIOUS AUDIO VISUAL SUPPLIES	849,876.00

Purpose: for APP 2023 1st Quarter - Audio and Visual Supplies

Philgeps Posting: Active Date: 2/24/2023 Category: AVDIO & VISUAL EQUIP.
 Closing Date: 2/28/23 Reference No.: 9510 F53

Interested suppliers are required to submit the following documents:

- | | |
|---|---|
| <input checked="" type="checkbox"/> Valid and Current Mayor's / Business Permit | <input checked="" type="checkbox"/> Latest Income / Business Tax Return |
| <input checked="" type="checkbox"/> Proof of PhilGeps Registration | <input checked="" type="checkbox"/> Omnibus Sworn Statement |
| | <input type="checkbox"/> Brochure, if applicable |

TSU Condition of Sale:

1. Delivery Schedule: 30 calendar days from receipt of approved PO/NTP
2. Bid Validity: 10 calendar days from submission of bids
3. Delivery Site: Supply and Property Management Unit, Tarlac State University
(045) 606-8159 / (045) 982-2605
4. Warranty shall be for a period minimum of three (3) months of expandable supplies, or a supplies/equipment after acceptance by the procuring entity of the delivered

Award of contract shall be made to the bidder with the lowest quotation for the subject goods which comply with the minimum technical specifications and other terms and conditions stated herein.

Any alteration, erasures, or overwriting shall be valid only if they are signed or initialed by the bidder or his/her duly authorized representative.

Submission of duly signed Price Quotation Form (Attachment 1-8) and eligibility documents is not later than 2/28/23 at the Procurement Unit, Admin Building Tarlac State University, Tarlac City.

Open submission may be done manually or through email at tsucanvassing@gmail.com / julietelaineacuna@yahoo.com

The penalty for late deliveries is one tenth (1/10) of one (1) percent of the cost of the underperformed portion for every day of delay. Once the cumulative amount of liquidated damages reaches ten (10%) percent of the contract price, the procuring entity shall rescind the contract without prejudice to other courses of action and remedies open to it.

The TSU reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract in accordance with Section 41 of R.A 9184 and its IRR, without thereby incurring any liability to the affected bidder or bidders.


ELENA MAY T. TEOFILO
 Head, Procurement Unit

PRICE QUOTATION

Date: 2/21/2023
 RFQ No. 115-2023
 PR No. 2023-02-074 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
1	piece	AUTOMATIC VOLTAGE REGULATOR, 10kVa Maximum Power Output: 10, 000VA, Servo Motor Control, Input Voltage:140-250 AC, Output, Voltage: 110-220 v AC, Single Phase, 50-60 Hz, 100% Pure copper wire Motor"	2		
2	unit	LAPEL, lapel microphone	20		
3	unit	LED LIGHT, CCT 5600K, CRI 95+, TLCI 95+ CQS 92, SSI (D56) 74, Output Wattage 200W, Power Consumption 250W, Operating Current 5.2A Operating Voltage, Battery 48V/5.5A, Operating Voltage, Power Supply Output 48V, Operating Voltage, Power Supply Input AC 100~240V 50/60HZ, Operating Temperature -20°C~45°C, Control Methods On-board, Sidus Link (Sidus Mesh™), Wireless Operating Range (Bluetooth) ≤ 80m, Screen Type LCD Firmware Upgradeable, Sidus Link OTA, Cooling Method Active Cooling, Power Supply Head Cable 3-pin X Max Head Cable Length 3m, AC Power Cable Locking IEC AC Power Cable (1.5m), Accessory Mount Bowsen Mount, Umbrella Holder Yes, Mounting 16mm 5/8in (Baby Pin), Weight, Lamp Head 1577g / 3.477lbs, Weight, Power Supply 813g / 1.792lbs, Weight, Total w/ Box 3960g / 8.73lbs, Dimensions, Lamp Head w/o Mounting Column 207*115*115mm / 8.15*4.528*4.528in, Dimensions, Lamp Head w/ Mounting Column 207*154*212mm / 8.15*6.063*8.346in, Dimensions, Lamp Head w/ Mounting Column & Reflector 313*185*247mm / 12.323*7.283*9.724in, Dimensions, Power Supply 170*84*30mm / 6.693*3.307*1.181in Dimensions, Carrying Box	2		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 2/21/2023
 RFQ No. 115-2023
 PR No. 2023-02-074 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
4	unit	LIGHT DOME , SE 33.5" (85cm) Key Features: 1.5- and 2.5-Stop Front Diffusers, 1.5-Stop Removable Interior Diffuser, 45° Fabric Grid Soft, Wraparound Quality of Light Top Features: 33.5" (85cm) Parabolic Softbox, 1.5 & 2.5 Stop Diffusion Cloths, Fabric Light Control Grid, Collapses Flat for Easy Travel, Bowens Accessory Mount, Perfect for Content Creators. Compatibility: Compatible with the Bowens Mount LED lights, such as the Amaran 100d, 100x, 200d, and 200x, as well as the Aputure LS 600d Pro, 300d II, 300x, and 120d II. It will also work with lights from other manufacturers who use this popular mount.	2		
5	unit	MEGAPHONE , Handheld, 15W, Rated Power Output 15W, Battery Life for voice use 14h, Colour Grey, Weight 1.1kg, Depth 346mm, Height 291 mm, Width 210 mm	3		
6	roll	MICROPHONE CABLE , Low Impedance Balanced, Thickness 7mm, 100m Roll	3		
7	piece	MICROPHONE CABLES , Connector 1 3-Pin XLR Male, Connector 2 3-Pin XLR Female Cable Length 20' / 6.1 m, Shielding 95% Spiral Wire Gauge 24 AWG, Contact Plating Silver"	4		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 2/21/2023
 RFQ No. 115-2023
 PR No. 2023-02-074 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
8	set	MICROPHONE , Wireless Microphone System (Receiver x 1; Microphone x 2) Receiver: Type: Tabletop, Antenna: 2 x Internal, Number of Audio Channels: 2, Audio I/O: 2 x XLR 3-Pin Male Bal. Mic/Line Output, 2 x 1/4" TS Balanced Mic/Line Output, Gain Range: 45 dB (5 dB Steps), Audio Output Level: XLR Outputs: 1/4" Outputs, Frequency Response: 50 Hz to 16 kHz -3 dB, RF Principle: Double Superheterodyne, Approximate RF Sensitivity: 52 dB / 3 µV, Squelch: Adjustable, 3 to 28 dBµV, Power Requirements: AC/DC Power Adapter : 12 VDC at 300 mA (Included, Microphones: RF Bandwidth: Up to 24 MHz, RF Channel Scanning: Manual, Max Operating Range: 100' / 30.5 m, Max Transmitters per Band: 10, Transmitter Type: Handheld, RF Output Power: 10 mW, Muting: Mute Switch, Frequency Response: 80 Hz to 14 kHz, Sync Method: 2.4 GHz QPSK, Antenna: Internal, Approximate RF Sensitivity: 52 dB / 3 mV, Power Requirements: Battery, Battery Type: 2 x AA, Muting: Mute Switch, Frequency response: 80 Hz to 14 KHZ, Sync Method: 2.4 GHz QPSK, Antenna: Internal, Approximate RF Sensitivity: 52 db / 3 m v, Power Requirements: Battery, Battery Type: 2 x AA, Snake Cable, Number of Channels: 24 (20 Send : 4 return), Length: 45 meter	1		
9	piece	MICROPHONE , Dynamic, Handheld, Polar Pattern: Cardioid, Frequency Response: 50Hz-15kHz Max SPL: 94dB SPL, Output Impedance: 150 ohms, Sensitivity: -54.5 dBV / Pa (1.88 mV), Color: Black, Connector: XLR	6		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 2/21/2023
 RFQ No. 115-2023
 PR No. 2023-02-074 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
10	piece	MICROPHONE , wireless, sensitivity 12dBuV (80db S/N), sensitivity range 12-32	6		
11	piece	MIXER AMPLIFIER , Power Rating 220 Watts @ 4 Ohms 130 Watts @ 8 Ohms (UA) 130 Watts @ 8 Ohms (H) Total Harmonic Distortion (THD) Less than 0.5 % (THD+N) +14 dB @ 20 Hz, 1 kHz, 20 kHz, GAIN control: all nominal Power Supply 120 V 60 Hz, 450 W, Dimensions 17.40 x 10.78 x 11.26" (442 x 274 x 286mm), Weight 22 lbs. (10 kg)"	1		
12	unit	MOBILE STABILIZER , Handle, Dimensions 2.4x1.9x6.4 inch (61.8x48.2x161.5 mm), Weight (including battery) 201 g, 501 g (including gimbal), Model OM150 Gimbal, Name Zenmuse M1, Model ZM01, Dimensions 4.92x4.29x3.57 inch (Folded) 125.06x109.15x90.98 mm, Weight 300g, Consumption 2.5 W, Angular Vibration Range ±0.03, Controllable Range Pan : ±150°, Roll : ±25°, Tilt : -125° to +35°, Mechanical Range Pan : ±165°, Roll : -50° to +90° Tilt : -140° to +50°, Max Controllable Speed 120°/s, Mobile Phone Width Range 2.31-3.34 inch (58.6-84.8 mm), Intelligent Battery, Model HB01-522365, Type LiPo, Capacity 980 mAh, Energy 10.8 Wh, Voltage 11.1 V, Charging Temperature 5° to 40° C (41° to 104° F), Operating Temperature 0° to 40° C (32° to 104° F), Wireless Model Bluetooth Low Energy 4.0	5		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 2/21/2023
 RFQ No. 115-2023
 PR No. 2023-02-074 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
13	unit	MULTICOLOR MINI LED LIGHT , Product Highlights 95% BT 2020 Gamut Coverage Full HSI Color Control 0 to 100% Dimming OLED Display with Control Wheel, Accessories Mount 1/4"-20 Female, Magnetic, Lighting Color Temperature 3200 to 6500K, Dimmable: Yes, 0 to 100%, Lens Number of LED 12, General Dimension 3.7 x 2.4 x 0.7" / 93 x 61 x 17 mm, Warranty 1 Year, Power/Battery Capacity: 2600 mAh Lithium-Ion Polymer (LiPo) Input connector: USB Type-C	3		
14	lot	RECORDING STUDIO ACCESSORIES , 5 Panel Foldable Studio Microphone Isolation Shield Recording Sound Absorber Foam Panel pop filter	1		
15	meter	ROYAL CABLE , Size: 8.0 mm, Cord: 3, Length: 30 meters	30		
16	unit	SOUND SYSTEM , 15" 2 Way 400W Powered Portable Sound System Plastic Cabinet, AC220V or DC12V (With built-in Rechargeable Batteries) With 2 Wireless Microphone With 2 Mic Input (1 XLR, 1 PL55) With FM Radio, Bluetooth, Guitar Input (Shared with Mic 2 input), USB & SD Port With 5 Band Equalizer and LCD Display With Aux / Line in and Line Out With Remote Control, Handle and WheelsVV	1		
17	piece	SPEAKER TRIPOD STAND , Material of Construction Aluminum, Height Adjustment Range Per Stand: 3.8 to 7.5' / 1.1 to 2.3 m, Mount Size 1.375" / 34.9 mm, 1.5" / 38.1 mm, Load Capacity Per Stand: 120 lb / 54.4 kg, Weight Per Stand: 6.1 lb / 2.8 kg"	4		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 2/21/2023
 RFQ No. 115-2023
 PR No. 2023-02-074 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
18	unit	SPEAKER , Portable and Wireless Bluetooth Speaker, dimension 15.70" x 17.20", weight 27.80,transducers 2x 216 mm(8") woofer, 2 x 70mm (2.75") tweeter, output power 800W RMS (IEC60268), power output 100-240 VAC~50/60Hz, frequency response 35Hz-20kHz (-6db)	6		
19	piece	SPEAKER , powered speakers, Power rating (W, Continuous) 500, Power rating (W,Peak) 1000, Frequency Response Hz (±3 dB) 50 - 20,000, Maximum SPL (peak dB)127, Coverage Pattern (Nominal) 90° x 60°, Weight (lbs) 39.0, Height (in) 27.8, Depth (in)14.4, Width (in)17.3, Height (mm) 707.0, Width (mm), 439.0, Depth (mm) 365.0, Weight (kg) 17.7	4		
20	unit	WIRELESS MICROPHONE SYSTEM , Dual-channel stereo receiver for cameras and mobile devices, Portable charging case for the transmitter and receiver, Vivid OLED display on both transmitter and receiver, Selectable Mono/Stereo output mode, Real time headphone monitor, Mic input and Line input, 8 hours battery life on one single charge, One button easy pairing, Display Transmitter 1 x OLED (Audio Level, Battery Status, Mute, Power, Signal Strength) Receiver 1 x CLED (Battery Status, Data Transmission, Mute, Power, Recharging, Sync, Transmitter Battery Status) Form Factor Microphone: Lavalier Maximum SPL 110 dB SPL. Polar Pattern Omnidirectional. Sound Field Mono. Range Operating Range: 328' / 100 m (Line of Sight). Input/Output Receiver Audio 1 x 1/8" / 3.5 mm TRS Female Unbalanced Mic Output 1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output Transmitter Audio 1 x 1/8" / 3.5 mm TRS Female Unbalanced Input. General, Cable Microphone: Length 4.1' / 1.2 m	4		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 2/21/2023
 RFQ No. 115-2023
 PR No. 2023-02-074 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
21	pair	LR CONNECTORS , Male and Female (Pair), Swiss made, Silver Contacts, Nickel Housing	30		
22	piece	WIRED MICROPHONES , Neodymium capsule design, Supercardioid pattern, Principle: Dynamic moving coil motor, Frequency Response : 80 – 18kHz, Sensitivity : -53 dBV (2.3mV) @ 1Pa, Impedance : 500 ohms, Max SPL >148dB, Note: with microphone box (box of three)	3		
23	piece	QUAD CONNECTORS , 3 External Line Return (XLR) F connectors, 3 XLR M connectors, 3 mic wires stereo 10M (each), Note: Connector Type: XLR, Cable Type: XLR, Compatible Devices: Speaker, microphone, Color: Black, Gauge: 21.0-24.0, Item Weight: about 10.4 ounces, Product Dimensions: 11.1 x 8.6 x 1.2 inches, Size: 10 Feet	1		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____



Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number 9510753
Procuring Entity TARLAC STATE UNIVERSITY
Title Various Audio Visual Supplies
Area of Delivery Tarlac

Solicitation Number: 115-2023 Trade Agreement: Implementing Rules and Regulations Procurement Mode: Shopping - Ordinary/Regular Office Supplies & Equipment (Sec. 52.1.b) Classification: Goods Category: Audio and Visual Equipment Approved Budget for the Contract: PHP 849,876.00 Delivery Period: 30 Day/s Client Agency:	Status Pending
Contact Person: Elena May T. Teofilo Unit Head Romulo Blvd. Tarlac City Tarlac Philippines 2300 63-2-092058494963 may_at_34@yahoo.com	Associated Components 3 Bid Supplements 0 Document Request List 0 Date Published 24/02/2023 Last Updated / Time 23/02/2023 10:21 AM Closing Date / Time 28/02/2023 13:00 PM

Description

For University use
 Line Items

Item No.	Product/Service Name	Description	Quantity	UOM	Budget (PHP)
1	AUTOMATIC VOLTAGE REGULATOR	10kVa Maximum Power Output: 10,000VA, Servo Motor Control, Input Voltage:140-250 AC, Output, Voltage: 110-220 v AC, Single Phase, 50-60 Hz, 100% Pure copper wire Motor"	2	Piece	44,000.00
2	LAPEL	lapel microphone	20	Unit	50,000.00
3	LED LIGHT, CCT 5600K	CRI 95+, TLCI 95+ CQS 92, SSI (D56) 74, Output Wattage 200W, Power Consumption 250W, Operating Current 5.2A Operating Voltage, Battery 48V/5.5A, Operating Voltage, Power Supply Output 48V, Operating Voltage, Power Supply Input AC 100~240V 50/60	2	Unit	40,000.00
4	LIGHT DOME	SE 33.5" (85cm) Key Features: 1.5- and 2.5-Stop Front Diffusers, 1.5-Stop Removable Interior Diffuser, 45° Fabric Grid Soft, Wraparound Quality of Light Top Features: 33.5" (85cm) Parabolic Softbox, 1.5 & 2.5 Stop Diffusion Cloths, Fabric Light Co	2	Unit	20,000.00
5	MEGAPHONE	Handheld, 15W, Rated Power Output 15W, Battery Life for voice use 14h, Colour Grey, Weight 1.1kg, Depth 346mm, Height 291 mm, Width 210 mm	3	Unit	9,000.00
6	MICROPHONE CABLE	Low Impedance Balanced, Thickness 7mm, 100m Roll	3	Roll	24,000.00

7	MICROPHONE CABLES	Connector 1 3-Pin XLR Male, Connector 2 3-Pin XLR Female Cable Length 20' / 6.1 m, Shielding 95% Spiral Wire Gauge 24 AWG, Contact Plating Silver	4	Piece	6,076.00
8	MICROPHONE	Wireless Microphone System (Receiver x 1; Microphone x 2) Receiver: Type: Tabletop, Antenna: 2 x Internal, Number of Audio Channels: 2, Audio I/O: 2 x XLR 3-Pin Male Bal. Mic/Line Output, 2 x 1/4" TS Balanced Mic/Line Output, Gain Range: 45 dB (5 d	1	Set	50,000.00
9	MICROPHONE	Dynamic, Handheld, Polar Pattern: Cardioid, Frequency Response: 50Hz-15kHz Max SPL: 94dB SPL, Output Impedance: 150 ohms, Sensitivity: -54.5 dBV / Pa (1.88 mV), Color: Black, Connector: XLR	6	Piece	57,000.00
10	MICROPHONE	wireless, sensitivity 12dBuV (80db S/N), sensitivity range 12-32	6	Piece	4,200.00
11	MIXER AMPLIFIER	Power Rating 220 Watts @ 4 Ohms 130 Watts @ 8 Ohms (UA) 130 Watts @ 8 Ohms (H) Total Harmonic Distortion (THD) Less than 0.5 % (THD+N) +14 dB @ 20 Hz, 1 kHz, 20 kHz, GAIN control: all nominal Power Supply 120 V 60 Hz, 450 W, Dimensions 17.40 x 10.78	1	Piece	38,000.00
12	MOBILE STABILIZER	Handle, Dimensions 2.4x1.9x6.4 inch (61.8x48.2x161.5 mm), Weight (including battery) 201 g, 501 g (including gimbal), Model OM150 Gimbal, Name Zenmuse M1, Model ZM01, Dimensions 4.92x4.29x3.57 inch (Folded) 125.06x109.15x90.98 mm, Weight 300g	5	Unit	50,000.00
13	MULTICOLOR MINI LED LIGHT	Product Highlights 95% BT 2020 Gamut Coverage Full HSI Color Control 0 to 100% Dimming OLED Display with Control Wheel, Accessories Mount 1/4"-20 Female, Magnetic, Lighting Color Temperature 3200 to 6500K, Dimmable: Yes, 0 to 100%, Lens Number of LED	3	Unit	30,000.00
14	RECORDING STUDIO ACCESSORIES	5 Panel Foldable Studio Microphone Isolation Shield Recording Sound Absorber Foam Panel pop filter	1	Lot	5,000.00
15	ROYAL CABLE	Size: 8.0 mm, Cord: 3, Length: 30 meters	30	Meter	21,000.00
16	SOUND SYSTEM	5" 2 Way 400W Powered Portable Sound System Plastic Cabinet, AC220V or DC12V (With built-in Rechargeable Batteries) With 2 Wireless Microphone With 2 Mic Input (1 XLR, 1 PL55) With FM Radio, Bluetooth, Guitar Input (Shared with Mic 2 input), USB &	1	Unit	13,000.00
17	SPEAKER TRIPOD STAND	Material of Construction Aluminum, Height Adjustment Range Per Stand: 3.8 to 7.5' / 1.1 to 2.3 m, Mount Size 1.375" / 34.9 mm, 1.5" / 38.1 mm, Load Capacity Per Stand: 120 lb / 54.4 kg, Weight Per Stand: 6.1 lb / 2.8 kg"	4	Piece	5,600.00
18	SPEAKER	Portable and Wireless Bluetooth Speaker, dimension 15.70" x 17.20", weight 27.80, transducers 2x 216 mm (8") woofer, 2 x 70mm (2.75") tweeter, output power 800W RMS (IEC60268), power output 100-240 VAC ~50/60Hz, frequency response 35Hz-20kHz (-6db)	6	Unit	239,400.00
19	SPEAKER	powered speakers, Power rating (W, Continuous) 500, Power rating (W, Peak) 1000, Frequency Response Hz (±3 dB) 50 - 20,000, Maximum SPL (peak dB) 127, Coverage Pattern (Nominal) 90° x 60°, Weight (lbs) 39.0, Height (in) 27.8, Depth (in) 14.4, Width (in)	4	Piece	36,900.00
20	WIRELESS MICROPHONE SYSTEM	Dual-channel stereo receiver for cameras and mobile devices, Portable charging case for the transmitter and receiver, Vivid OLED display on both transmitter and receiver, Selectable Mono/Stereo output mode, Real time headphone monitor, Mic input and	4	Unit	80,000.00

21	LR CONNECTORS	Male and Female (Pair), Swiss made, Silver Contacts, Nickel Housing	30	Pair	12,000.00
22	WIRED MICROPHONES	Neodymium capsule design, Supercardioid pattern, Principle: Dynamic moving coil motor, Frequency Response : 80 – 18kHz, Sensitivity : -53 dBV (2.3mV) @ 1Pa, Impedance : 500 ohms, Max SPL >148dB, Note: with microphone box (box of three)	3	Piece	13,500.00
23	QUAD CONNECTORS	3 External Line Return (XLR) F connectors, 3 XLR M connectors, 3 mic wires stereo 10M (each), Note: Connector Type: XLR, Cable Type: XLR, Compatible Devices: Speaker, microphone, Color: Black, Gauge: 21.0-24.0, Item Weight: about 10.4 ounces, Produc	1	Piece	1,200.00

Other Information

The bidders must download the attached documents in the associated component section.

Created by Elena May T. Teofilo

Date Created 23/02/2023

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.